

AB5605C

Audio Player Microcontroller

Versions: 0.0.4
2023.01.10



Declaration

Copyright © 2022, [www. bluetrum.com](http://www.bluetrum.com).

All Rights Reserved. No Unauthorized Distribution.

Bluetrum reserves the right to make changes without further notice to any products herein to improve reliability, function or design.

For further information on the technology, product and business term, please contact Bluetrum Company.

For sales or technical support, please send email to the address:

Sales: sales@bluetrum.com

Technical: project@bluetrum.com

Revision History

Date	Version	Comments	Revised by
2021-08-10	0.0.1	First draft	Leo
2022-01-22	0.0.2	Update QDID	Leo
2022-08-24	0.0.3	Update QDID	Leo
2023-1-10	0.0.4	Update Product Features	Leo

Table of Contents

TABLE OF CONTENTS	2
1 PRODUCT FEATURES.....	3
2 PACKAGE DEFINITION.....	4
2.1 PIN ASSIGNMENT	4
2.2 PIN DESCRIPTIONS	4
3 CHARACTERISTICS.....	8
3.1 PMU PARAMETERS	8
3.2 IO PARAMETERS	8
3.3 AUDIO DAC PARAMETERS.....	9
3.4 AUDIO ADC PARAMETERS.....	9
3.5 BT PARAMETERS.....	10
3.6 CURRENT PARAMETERS.....	10
4 PACKAGE INFORMATION.....	11

1 Product Features

CPU and Flexible IO

- High performance 32bit RISC-V processor Core with DSP instruction
- RISC-V typical speed: 125MHz
- Program memory: internal 4M bit flash
- Internal 128KB RAM for data and program
- Flexible GPIO pins with Programmable pull-up and pull-down resistors
- Support GPIO wakeup or interrupt

Bluetooth Radio

- Compliant to Bluetooth 5.3 (QDID:194248);
- TX output power +6dBm in typical;
- RX Sensitivity with -90.5dBm @EDR;

FM Tuner

- Support frequency band 76~108MHz;
- Auto search tuning;
- Programmable de-emphasis(50/75uS);
- Receive signal strength indicator (RSSI);

Audio Interface

- Audio codec with 16bit mono DAC and 16bit mono ADC;
- Support flexible audio EQ adjust;
- Support Sample rate 8, 11.025, 12, 16, 22.05, 32, 44.1 and 48KHz;
- 2 channels Analog MUX;
- One channel MIC amplifier input;
- High performance mono audio ADC with 90dB SNR;
- High performance audio DAC with 96dB SNR, with headphone amplifier output;

Peripheral and Interfaces

- Three 32-bit timers;
- Three multi-function 32-bit timers, support Capture and PWM mode;
- WatchDog;
- Three full-duplex UART;
- SPI;
- IR controller;
- SD Card Host controller;
- Full speed USB 2.0 HOST/DEVICE controller;
- Sixteen Channels 10-bit SARADC;
- Build in PMU, such as LDO;

Package

- SSOP24;

Temperature

- Operating temperature: -40°C to +85°C;
- Storage temperature: -65°C to +150°C;

2 Package Definition

2.1 Pin Assignment

1	VDDDAC	DACL	24
2	AGND	PF0	23
3	FM_ANT	MICL/PF2	22
4	PE7	PA5	21
5	PE6	PA6	20
6	PE0	PA7	19
7	VDDIO	USB_DP/PB3	18
8	VBAT	USB_DM/PB4	17
9	DGND	BT_OSCO	16
10	VDDBT	BT_OSCI	15
11	PB2	BT_ANT	14
12	PB1	PWRKEY	13

2.2 Pin Descriptions

Table 2-1 SSOP24 pin description

Pin No.	Name	Type	Function
1	VDDDAC	PWR	DAC power
2	AGND	GND	DAC Ground
3	FM_ANT	A	FMRX ANT
4	PE7	I/O	ADC9 AUXR2 SDDAT0-G3 SPI1DO -G4 TX0-G4

			HSTRX-G4 PWM2-T4-G1 TMR4CAP_G1/IR_G8 IISLRCLK-G2 PE7
5	PE6	I/O	SPDIF2 ADC8 AUXL2 SDCLK-G3 SPI1CLK-G4 RX0-G4 HSTRX-G9 FMOSC-G6 PWM1-T4-G1 TMR3CAP_G7/IR_G7 IISCLK-G2 PE6
6	PE0	I/O	SPI0DI-G3 TX0-G5 PWM0-T3-G4 TMR3CAP_G5/IR_G5 IISMCLK-G2 PE0
7	VDDIO	PWR	VDDIO power output
8	VBAT	PWR	VBAT power input
9	DGND	GND	Digital Ground
10	VDDBT	PWR	BT power
11	PB2	I/O	ADC4 AUXR1 SDDAT0-G2 SPI1DO -G3 TX0-G2 TX2-G2 HSTRX-G2 PWM2-T3-G1 PB2
12	PB1	I/O	ADC3 AUXL1 SDCLK-G2 SPI1CLK-G3 RX0-G2 RX2-G2 HSTRX-G7 FMOSC-G4 PWM1-T3-G1

			TMR3CAP_G4/IR_G4 PB1
13	PWRKEY	A	Power key input
14	BT_ANT	A	BT ANT
15	BT_OSCI	A	26M OSC input
16	BT_OSCO	A	26M OSC output
17	USB_DM/PB4	I/O	USB DM ADC6 SDDAT0-G4/G6 SPI0CLK-G3 RX0-G3 HSTRX-G8 PWM1-T3-G2 PB4
18	USB_DP/PB3	I/O	USB DP ADC5 SDDAT0-G5 SDCMD-G6 SPI0DO-G3 TX0-G3 HSTRX-G3 PWM0-T3-G2 PB3
19	PA7	I/O	ADC2 AUXR0 SDDAT0-G1 SPI1DO-G2 SPI1DATA-G2 TX0-G1 TX1-G1 HSTRX-G1 PWM2-T5-G1 IISDI-G1 PA7
20	PA6	I/O	ADC1 AUXL0 SDCLK-G1/G4/G5/G6 SPI1CLK-G2 RX0-G1 RX1-G1 HSTRX-G6 FMOSC-G2 PWM1-T5-G1 TMR3CAP_G2/IR_G2 IISDO/DAT-G1

			PA6
21	PA5	I/O	ADC0 SDCMD-G1/G4/G5 SPI1DI-G1 SPI1DI-G2 FMOSC-G1 PWM0-T5-G1 TMR3CAP_G1/IR_G1 IISCLK-G1 PA5
22	MICL/PF2	I/O	MICL SPDIF5 ADC10 SPI1DO -G5 TX0-G7 PWM0-T3-G3 TMR5CAP_G1/IR_G9 PF2
23	PF0	I/O	SPDIF3 AUXL3 SPI1DI-G5 TX0-G6 PWM1-T4-G2 PF0
24	DACL	A	DAC L

Note: I/O: Digital input/output; I : Digital input; A : Analog Pin; PWR: Power Pin; GND: Ground.

3 Characteristics

3.1 PMU Parameters

Table 3-1 PMU voltage input Parameters

Sym	Characteristics	Min	Typ	Max	Unit	Conditions
VUSB	Charger Voltage input	4.6	5.0	5.5	V	
VBAT	Voltage input	2.4	3.3	4.5	V	

Table 3-2 3.3V LDO Parameters

Sym	Characteristics	Min	Typ	Max	Unit	Conditions
VDDIO	3.3V LDO voltage output	-	3.3	-	V	Light Loading condition
Δ VDDIO	Output Mismatch 1-sigma	-	56	-	mV	VDDIO=3.3v
ILOAD	Maximum output current	-	-	150	mA	@VBAT=3.6v
ISC	Short Circuit Current Limit	-	-	300	mA	@VBAT=3.8v

Table 3-3 1.2V LDO Parameters

Sym	Characteristics	Min	Typ	Max	Unit	Conditions
VDDBT	1.2V LDO voltage output	-	2.8	-	V	Light Loading condition
Δ VDDBT	Output Mismatch 1-sigma	-	48	-	mV	VDDBT=1.2v
ILOAD	Maximum output current	-	-	20	mA	@VBAT=3.0v
ISC	Short Circuit Current Limit	-	-	40	mA	@VBAT=3.8v

3.2 IO Parameters

Table 3-4 I/O Parameters

GPIO—Electrical Characteristics							
Symbol	Description	Related GPIO	Min	Typical	Max	Units	Conditions
VIL	Low-level input voltage		-0.3		1.27	V	VDDIO=3.3V
VIH	High-level input voltage		2.03		3.6	V	VDDIO=3.3V
Driver Ability 1	Output Driver Ability 1			32		mA	VDDIO=3.3V
Driver Ability 0	Output Driver Ability 0			8		mA	VDDIO=3.3V
RPUP0	Internal pull-up resistor 0		8	10	12	K Ω	
RPUP1	Internal pull-up resistor 1		0.24	0.3	0.36	K Ω	
RPUP2	Internal pull-up resistor 2		160	200	240	K Ω	
RPDN0	Internal pull-down resistor 0		8	10	12	K Ω	
RPDN1	Internal pull-down resistor 1		0.24	0.3	0.36	K Ω	

GPIO—Electrical Characteristics							
RPDN2	Internal pull-down resistor 2		160	200	240	KΩ	

3.3 Audio DAC Parameters

Table 3-5 Audio DAC Parameters

Sym	Characteristics	Min	Typ	Max	Unit	Conditions
SNR		-	96	-	dB	VDDDAC cap=1uF with A-wt filter Output -3dBV Fin=1KHz
THD+N		-	-70	-	dB	VDDDAC cap=1uF with A-wt filter Output -3dBV with 10K loading Fin=1KHz
Output Range	Maximum output voltage	-	2.6		Vpeak-peak	32ohm Loading

3.4 Audio ADC Parameters

Table 3-6 Audio ADC Parameters

Sym	Characteristics	Min	Typ	Max	Unit	Conditions
SNR		-	90	-	dB	VDDDAC cap=1uF with A-wt filter Input sine amplitude, 850mV RMS Fin=1KHz
THD+N		-	-76	-	dB	VDDDAC cap=1uF with A-wt filter Input sine amplitude, 850mV RMS Fin=1KHz.
Input Range	Input sine wave peak amplitude	0		VCM	V	From aux input, aux 0db gain, VCM represent VCM voltage.

3.5 BT Parameters

Table 3-7 BT Parameters


Characteristics	Min	Typical	Max	Unit	Conditions
Maximum Transmit Power	-	-	7	dBm	
RMS DEVM	-	5.5	-	%	Maximum TX power 2-DH5 packet
Peak DEVM	-	12.5		%	
EDR Relative Transmit Power		-0.2		dB	
Sensitivity @ Basic Rate		-88.3		dBm	BER=0.1%, using DH5 packet
Sensitivity @ EDR		-90.5		dBm	BER=0.01%, using 2-DH5 packet

3.6 Current Parameters

Table 3-8 Current Parameters

Sym	Characteristics	Min	Typ	Max	Unit	Conditions
IRTC	RTC mode current	-	4	-	uA	4.2V input, room temp.
Sleep	Sleep current	-	500	2000	uA	3.3V input, room temp

4 Package Information



SYMBOL	MILLIMETER		
	MIN	NOM	MAX
A	—	—	1.75
A1	0.10	0.15	0.25
A2	1.30	1.40	1.50
A3	0.60	0.65	0.70
b	0.23	—	0.31
b1	0.22	0.25	0.28
c	0.20	—	0.24
c1	0.19	0.20	0.21
D	8.55	8.65	8.75
E	5.80	6.00	6.20
E1	3.80	3.90	4.00
e	0.635BSC		
h	0.30	—	0.50
L	0.50	—	0.80
L1	1.05REF		
θ	0	—	8°



Contact us

Address: 深圳市南山区沙河街道高发社区侨香路 4068 号智慧广场 A 栋
1301-1

E-mail: info@bluetrum.com

Website: www.bluetrum.com